Olympus+ Ceramic Water Filter

PRODUCT OF GREECE
MANUFACTURER:
CENTER PLUS SA

TO QUICKLY INSTALL A NEW UNIT OR CHANGE THE CERAMIC CARTRIDGE

INSTALLING THE UNIT ON THE TAP

1) Remove the aerator from your tap spout. Screw on the filter valve (diverter) in place of the aerator. If your tap has a female thread, use the nipple supplied in the pack **(see picture (10) in the detailed instructions)**.
2) Remove the plastic wrapping from the ceramic cartridge. Screw the cartridge clockwise in the centre of the filter base, loosely, **without overtightening it, so as not to break its plastic thread or the ceramic, and also to avoid reducing the water flow from the unit's tap.** Now screw the metal cap firmly onto the filter base, turning it to the right.
3) The first time and every time you change the cartridge, **let the water run for 10 minutes (on first use, a little black water may come out as the activated carbon is flushed)**. **Leave the filter idle for 24 hours**. Then, once you have turned it on and let it run for 2-3 minutes, the filter is ready for use. Also, if the filter is left unused for more than 3 days, let the water run for 2-3 minutes.
   CAUTION **If, on first use, the filtered/unfiltered water diverter is stiff to switch over, apply more force to turn it.**
4) Every 3-4 months, or whenever **there is a noticeable drop in water flow** from the unit's tap (which means that the filter's ceramic cartridge has become 'clogged' with sediment, rust, mud, slime, limescale, etc.), remove the cartridge from the unit and, under the cold tap **(without detergents)**, scrub its entire surface thoroughly with the **scouring side of a dish sponge**, **or with a harder wire scourer or even with emery cloth (grit 80)**, to clean it and improve the water flow. After rinsing it thoroughly, refit it in place.
5) **Never pass hot water through the filter.**

CHANGING THE CERAMIC CARTRIDGE (filter spare part)

6) Unscrew the unit's metal cap anticlockwise **(as described in paragraph 2)** and screw the new replacement cartridge clockwise in the centre of the base, **loosely**, without overtightening it **(see paragraph 2).**
7) Screw the metal cap back on and **follow the instructions in paragraphs 2 and 3 above.**

Detailed instructions and pictures of the unit and its parts can be found in the 4-page warranty leaflet supplied with your unit.

v.7

CENTER PLUS SA

● ACHARNES: 87 Karamanli Ave (13679)
● ATHENS: 40 Veranzerou St (10432)
● www.olympusplus.com ● www.olympusplus.gr ● www.olympusplus.cy
● www.olympusplus.ro ● www.olympus-plus.bg ● E-mail: info@centerplus.gr